



Class 1

Building Product Information Requirement

Product Name:

CEZANNE 1000X1000 ROUND MOULDED WHITE - CORNER WASTE

Product Identifier:

1CZ2W11RMCRC

Product Description & Specifications:

The Cezanne Round Sliding Door Acrylic Wall Shower is a popular choice for builders and renovators with limited space. Incorporating a space saving three panel sliding door in a unique rounded shape, you don't need to worry about bumping your shower door into your other bathroom furniture. A Sure Seal Tray and Moulded or Flat Acrylic Walls give you versatility in your shower choice and you can choose between White and Bright Joinery to best suit your style. With a contemporary bar handle, magnetic door closure and chrome easy clean waste, the Cezanne Round Sliding Door Acrylic Wall Shower is the perfect option for you.

- 70mm SureSeal™ Tray includes 20mm upstand for a leak free shower
- Unique Round Shape
- Chrome Easy Clean Waste
- 1970mm High Enclosure
- Space Saving Sliding Door
- White or Bright Joinery
- 6mm Safety Glass
- QCS15665 Chrome Double Sided Bar Handles 126mm (hole pitch)
- Magnetic Door Closure
- 5 Year Warranty with 12 month warranty on drip strips and vertical seals.

Image:



Manufacturer:

Tile Depot Approved supplier. All our manufacturers produce material to comply with the technical requirements and tolerances prescribed by ISO13006.

Legal and Trading name of the importer:

www.tiledepot.co.nz

83 Harris Rd, East Tamaki, Auckland



Tile Depot LP

NZBN: 9429049866773

Address: 83 Harris Rd, East Tamaki, Auckland, New Zealand

Website: www.tiledepot.co.nz

Email: info@tiledepot.co.nz

Phone: 0800 845 3337



Relevant Building Code Clauses:

D1 – Access Routes Refer Section 2.0

Requires access routes to have an adequate slip resistance surface. For housing this requirement applies only to the access route on the approach to the main entrance and not inside that entrance and not on the approach to other entrances. The internal access routes of housing, including kitchens and bathrooms shall be assumed to be dry in normal use. When specifying suitability of a selected tile refer to D1 2.0 in conjunction with the slip rating of the material provided.

E3 – Internal Moisture

Clause 3.1.1 references product porosity. Ceramics are a commonly accepted industry solution and porcelain tiles have a very low water absorption level (less than 0.5%). Higher porosity ceramic and natural stone products can be presented as an alternative solution. Ceramic wall tiles have an impervious glaze and a protective layer called an engobe. Natural stone can be sealed with a penetrating sealer. Grouts can be sealed or the use of epoxy grouts will minimise water penetration to the substrate. If in doubt check with the specifier prior to installation.

C3 – Protection from Fire

The Building code relating to fire rating regulations and standards requires specifiers to provide documentation such as fire certificates for materials used in construction. Ceramics are in itself fire-resistant material, most being manufacturer in excess of 1200 degree Celsius. Testing and providing such certification is therefore not relevant to the ceramics industry.

Ceramics are non-combustible and they do not release fumes or toxic gases in the event of a fire. Ceramics contain no sealants, waxes or other chemicals that could release VOC's into the environment. Ceramics do not pose a risk of spreading or intensifying a fire.



Statement on how this product is expected to contribute to compliance:

D1 – Access Routes – subject to intended use, location and slip resistance properties of selected tile.
C3 – Protection from Fire - Ceramics do not pose a risk of spreading or intensifying a fire.

Limitations on the use of this building product:

Porcelain and ceramic tiles will not perform without a suitable substrate. It is the responsibility of the specification designer and / or installer to ensure an adequate substrate prior to installation.

Refer to the individual product specifications which outline characteristics including material, surface finish, size, PEI, weight and slip rating where applicable.

Installation Requirements:

Tiles must be installed by a competent trades person. Relevant resources include:

- MBIE Guide to tolerances
- Branz Good Practice guide – Tiling
- NCTC – Tile & Tiling Guide
- BCITO training and accreditation
- Installation systems from reliable adhesive & waterproofing manufacturers

Tiles are one of the most hygienic and easily maintained wall and floor surfaces available. A simple routine clean is required regularly with suitable tile specific cleaning agents.

This product is not subject to a warning or ban under section 26 of the Building Act 2004

Version 1

Date: July 27 2025