



# CLASSIC OAK RIDGE 235 X 1525

## Description

Sold per box 2.506m<sup>2</sup>, 72 Hour moisture protect, High density HDF Body, 40 unique faces

Please ensure installation instructions are followed (printed on the flyer in each box). Any breach of instructions may cause performance issues and will void the product warranty.

-10mm perimeter gap required. Areas that are exposed to direct sunlight and temperatures over 40°C or subject to significant temperature fluctuations, the expansion joint should be increased to 12mm.

-Floorprep: less than 5mm over 3m

-Skirtings must not be siliconed (only wet areas)

PLEASE READ: Floor to ceiling windows coupled with the New Zealand sun can create floor surface temperatures over 70°C. Classic Oak flooring is manufactured to be stable in low and high temperatures (0-50°C). However, your floor should be protected from extreme temperatures and strong direct sunlight using interior temperature and humidity control (recommended temperatures 10 - 30°C), window tinting, awnings and/or curtains/ blinds. Dramatic temperature changes and/or extreme humidity can cause joints to lip/gap and prolonged direct sunlight may cause fading. We strongly recommend the use of a vapor barrier, subfloor moisture can lead to installation failure, alkali salt build up damage to joints and a potential mold source.

For more information, data sheets and installation guides <https://www.tiledepot.co.nz/classic-oak>





~~\$69.90~~  
**\$55.92** per m<sup>2</sup>  
(incl GST)

Out of Stock

## Specifications

Finish:	MATT
Material:	LAMINATE
Origin:	CHINA
Size:	235 x 1525
Variation:	3
Weight:	8.8 kg per m <sup>2</sup>
m <sup>2</sup> Per Box:	2.5
Tiles Per Pack:	7

