

## **TENACITY GROVE OAK 194 X 1215**

## Description

Sold per box 1.414m2/box

12 unique faces

Please ensure installation instructions are followed (printed on the back of each box). Any breach of instructions may cause performance issues and will void the product warranty.

MgO Flooring, 100% waterproof, 100% PVC free. Angle to Angle installation.

Floating flooring system with pre attached underlay.

- -6mm perimeter gap required. Areas that are exposed to direct sunlight and temperatures over 40°C or subject to significant temperature fluctuations, the expansion joint should be increased to 10mm.
- -Not suitable for areas exceeding 50°C direct sunlight temperatures.
- -Floor prep: less than 5mm over 3m.
- -A moisture barrier is recommended on all installs over concrete.
- -Skirtings must be removed prior to installation.
- -Skirtings should not be siliconed in open planed areas
- -Please read E3 alternate flooring requirements for wet areas (available for download)
- -Not suitable over underfloor heating.





\$114.90 \$57.45<sub>per m2</sub>

Stock
Very High (200+ m2)

## **Specifications**

Finish:	MATT
Material:	MgO
Origin:	CHINA
Size:	194 x 1215
Variation:	2
Weight:	14.2 kg per m <sup>2</sup>
Weight: Sealing Required:	14.2 kg per m²
Sealing Required:	No
Sealing Required:  Colour:	No Grey



